

# 1200

### POLYURETHANE HIGH GLOSS

## **Product Description**

MCM #1200 Series Polyurethane High Gloss enamel is a high solids, hi hide coating reinforced with polyurethane resin. Formulated to withstand tropical and subtropical climate conditions. It provides long term gloss retention and is resistant to blistering and mildew when applied properly to prepared surfaces based on the manufacturer's recommendation. 1200 Polyurethane High Gloss has excellent UV resistance which results in resistance to color fading over long time periods. It is also high in zinc for rust resistance and high in durability for salt spray resistance.

#### **Product Features**

- High Gloss
- Tropical Climate Resistant
- Blister & Mildew Resistant
- Excellent Gloss & Color Retention
- Maximum Adhesion & Hardness
- Lead & Mercury Free
- Salt Spray Resistant
- Laboratory Tested
- Satisfaction Guaranteed

## Recommended Uses

- Machinery
- Boats
- Tractors
- Piping
- Storage Tanks
- Floors
- Heavy Equipment
- Industrial Structures
- Tools
- Virtually any pre-primed structure

# **Surface Preparation**

All surfaces must be clean and dry. Glossy surfaces should be dulled by sanding or liquid dull solution. Remove any traces of mildew. Previously painted or bare surfaces should be primed with MCM #1215 or #1216 primers.

# Spreading rate

On primed surfaces up to 400 square feet per gallon, depending on previous color, surface porosity and application

## **Drying Time**

Rapid Dry: dries to touch in 2 hours and may be recoated immediately.

Regular Dry: dries to touch in 5 hours and maybe recoated after 10 hours.

Drying times may vary depending on temperature, humidity & air movement.

## Clean Up

Clean hands, tools and equipment promptly with Mineral Spirits or Naptha.

### **Application**

May be sprayed, brushed or rolled. If required, it can be thinned with mineral spirits.

#### **CAUTION! COMBUSTIBLE**

Keep away from heat & flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use. USE ADEQUATE VENTILLATTION.

#### **KEEP OUT OF REACH OF CHILDREN**

<u>Limitation of Liability:</u> This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.