



1700

ALKYD SEMI-GLOSS

Product Description

MCM #1700 premium semi-gloss enamel is an interior or exterior semi gloss enamel. Formulated to withstand tropical and sub-tropical climates. Has long term gloss retention properties as well as extreme levels of resistance to blistering and mildew. #1700 has excellent UV resistance & color fade protection. This product is also rust inhibitive and salt spray resistant.

Product Features

- Semi-Gloss Enamel
- Formulated for Tropical Climates
- Blister & Mildew resistant
- Color lock technology
- Excellent adhesion
- Oil-Based
- Easy to apply
- Rust Resistant
- Non Yellowing
- Satisfaction Guaranteed

Application

May be applied by brush, roller or spray. It is not recommended to reduce. Apply generously and spread evenly to obtain uniformity of sheen, color and thickness. Do not apply in direct sunlight. Contact MCM for further questions 863-984-9496

Recommended Uses

- For interior or exterior use
- Use over existing oil based coatings
- Wood
- Plaster
- Drywall
- Stucco
- Metal
- Cabinets
- Any primed surface

Surface Preparation

All surfaces must be clean, sound and dry. Dull gloss surfaces by sanding or applying liquid sander. Fill holes and cracks with appropriate compound. Previously painted surfaces in good condition are not required to prime. New wood should be primed with #2800 or #2600. Metal should be primed with #1215 or #1216.

Spreading Rate

On primed wood and masonry up to 400 square feet per gallon. Depending on previous color, surface porosity and application method.

Drying Time

Dries to touch in 4 hours. May be recoated after 24 hours. Dry times may vary depending on temperature, humidity and air movement.

Clean Up

Clean hands, tools and equipment promptly with mineral spirits.

Characteristics

Finish: Semi Gloss
Generic Type: Alkyd
Solvent: Mineral Spirits
Weight per Gallon: 9.7lb
Flash Point: 105 Degrees F

CAUTION! COMBUSTIBLE

KEEP OUT OF REACH OF CHILDREN

Keep away from heat and flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use.

USE ADEQUATE VENTILATION

LIMITATION OF LIABILITY

This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

WARNING! Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.