



2700

Alkyd Primer Sealer

Product Description

MCM #2700 Stain Block Alkyd Primer is formulated to block stains and prevent bleed through. It is effective in preventing bleed-thru of wood knots, ink, crayon, water stains, etc. Compatible for virtually any surface other than galvanized. It is also excellent for smoke damage.

Product Features

- High Hide
- Blocks Stains
- Works over oil-based coatings
- Blocks Mildew
- High Solids
- Maximum Coverage
- 1 hour dry for fast recoat
- Can be coated over with latex
- Works on soot

Recommended Uses

- For interior or exterior use
- Use over existing oil based coatings
- Wood
- Plaster
- Drywall
- Stucco
- Metal
- Cabinets

Surface Preparation

All surfaces must be clean, sound and dry. Dull glossy surfaces. Fill holes and cracks with appropriate compound. Previously painted surfaces require no special priming. Chalky surfaces should be sealed with #40 surface conditioner prior

Spreading Rate

300-400 square feet per gallon depending on surface condition.

Drying Time

Dries to touch in 4 hours. May be recoated after 24 hours. Dry times may vary depending on temperature, humidity and air movement.

Clean Up

Clean hands, tools and equipment promptly with mineral spirits.

Characteristics

Finish: Low Luster
Generic Type: Alkyd
Solvent: Mineral Spirits
Weight per Gallon: 12.6lb
Flash Point: 105 Degrees F
V.O.C. 339 g/l

Application

May be applied by brush, roller or spray. It is not recommended to reduce. Apply generously and spread evenly to obtain uniformity. Do not apply in direct sunlight. Contact MCM Paints for further questions 863-984-9496

CAUTION! COMBUSTIBLE KEEP OUT OF REACH OF CHILDREN

Keep away from heat and flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use.
USE ADEQUATE VENTILATION

LIMITATION OF LIABILITY

This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

WARNING! Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.