



# 6000

Pro-Series Flat Acrylic

## Product Description

MCM Pro-Series Flat Acrylic is an economical go-to coating for several different applications.

## Product Features

- High Hide formula
- Mildew resistant
- Perfect for ceilings
- Tintable to any color
- Easy application
- Hides blemishes
- Easy clean up
- Available in black for parking lots
- Works well for field marking

## Recommended Uses

- Drywall
  - Wood
  - Plywood
  - Masonry
  - Galvanized metal
  - Aluminum
  - All primed surfaces
- Especially recommended for homes, hotels, factories, hospitals, schools, offices, and other buildings subject to harsh environment in tropical and subtropical climates.

## Surface Preparation

All surfaces must be clean, sound and dry. Dull gloss surfaces by sanding or applying liquid sander. Fill holes and cracks with appropriate compound. Use #40 surface conditioner before application if chalk is present.

## Application

May be applied by brush, roller or spray. Apply generously to achieve maximum coverage.

For any other instruction call  
MCM Paints 863-9496

## Spreading Rate

300-400 sq. ft. per gallon depending on the type of application and the porosity of the surface being painted.

## Drying Time

Dries to touch in 30 minutes and can be recoated in 2-3 hours or overnight depending on drying conditions.

## Clean Up

Clean hands, tools and equipment promptly with warm soapy water.

## Characteristics

**Finish:** Flat  
**Color:** White and can be tinted to any custom color  
**Generic Type:** Acrylic  
**Solvent:** Water  
**Weight per Gallon:** 11.8 lbs

**CAUTION!**  
**KEEP FROM FREEZING**  
Do not take internally. Close container after each use.  
**USE WITH ADEQUATE VENTILATION.**  
**KEEP OUT OF REACH OF CHILDREN**

**LIMITATION OF LIABILITY**  
This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

**WARNING!** Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.